

CBD20-490

2.0 Ton Electric Pallet Truck

Advantages

- ⊙ High running speed 11km/h.
- ⊙ EPS-Mute, energy saving, lighter.
- ⊙ AC Driving System-Low noise, quiet, without carbon brush and free maintenance.
- ⊙ Electric Lifting-Rapid, efficient, electricity limit switch is Standard.
- ⊙ AC Controller-Stepless, strong power, multiple automatic protection.
- ⊙ Excellent Design-Easily in and out of the double tray.
- ⊙ Intelligent Control-Curve automatically slow down, more safety.
- ⊙ Safer-Surrounded by half a cockpit, Care for your safety.

Options

- ⊙ 7km/h lower travel speed.
- ⊙ 320Ah Battery capacity.
- ⊙ Side-way Battery.

EPS | AC | 11km/h

Steering automatic deceleration

Fork suitable for reversible pallet

Excellent quality, Best service



HELI CBD20-490

| Feature | | |
|--|------|------------------------------|
| Model | | CBD20 |
| Configuration No. | | 490 |
| Loading capacity | kg | 2000 |
| Load center | mm | 600 |
| Wheel base | mm | 1569 |
| Operating type | | Ride On |
| Wheels | | |
| Wheels type | | PU |
| Wheel quantity Driving wheel/Balance wheel/Bearing wheel | | 1/2/4 |
| Driving wheel size | mm | ∅248×75 |
| Bearing wheel size | mm | ∅84×80(Double wheels) |
| Balance wheel size | mm | ∅115×55 |
| Dimension | | |
| Min.fork lowered height | mm | 85 |
| Max.fork lifting height | mm | 205 |
| Max.lifting height | mm | 120 |
| Overall fork width | mm | 550/600/650/685 |
| Inside width between forks | mm | 210/260/310/345 |
| Fork length | mm | 1150/1200 |
| Fork width | mm | 170 |
| Fork thickness | mm | 75 |
| Overall length | mm | 2465 |
| Overall width | mm | 790 |
| Overall height(With handle) | mm | 1170 |
| Overall height(Without handle) | mm | - |
| Min.Turning radius | mm | 2278 |
| Min.Aisle width for pallets 800×1200 | mm | 2568 |
| Min.Aisle width for pallets 1000×1200 | mm | 2589 |
| Performance | | |
| Travel speed,laden/unladen | km/h | 10/10 |
| Lift speed,laden/unladen | mm/s | 20/25 |
| Lowering speed,laden/unladen | mm/s | 40/30 |
| Gradeability,laden/unladen | % | 15/10 |
| Electrical configuration | | |
| Drive motor | kW | AC 3 |
| Lift motor | kW | DC 1.2 |
| Steering motor | kW | DC 0.15 |
| Battery voltage / capacity | V/Ah | 24/320 |
| Brake | | Electromagnetic/Regenerative |
| Controller | | CURTIS |
| Weight | | |
| Battery weight | kg | 250 |
| Service weight with battery | kg | 875 |

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



HELI CANADA

5705, place Kubota
 Drummondville (Qc)
 Canada, J2B 6V4
 1-833-HELICAN
 info@heliforklift.ca
 heliforklift.ca



Our products are subject to improvements and changes without notice.